

## Catalyst 1027 polyurethane catalyst 1027 foaming retarder 1027

### Catalyst 1027

Product properties:

Name: Catalyst 1027

Alias: catalyst 1027, polyurethane catalyst 1027, 1027, delay catalyst 1027, foaming retarder 1027, foaming retarder, DABCO 1027

Appearance: light yellow liquid

Viscosity (25°C, mPa.s): 75

Density (25°C, g/cm<sup>3</sup>): 1.1

Water-soluble: soluble in water

Flash point (PMCC, °C): 95

Hydroxyl value (mgKOH/g): 1195

Catalyst 1027 Jeffcat Z-130 Polyurethane Catalyst 1027 Delay Catalyst 1027 DABCO 1027 Foaming Delay Agent 1027

Polyurethane catalyst 1027 is a delayed tertiary amine catalyst (diluting solvent: ethylene glycol). It has high reactivity and high selectivity, and has high catalytic efficiency for the reaction of polyol and isocyanate. DABCO 1027 can prolong the gel time, increase the early fluidity, accelerate the later curing, and at the same time can accelerate the product demoulding. It is an excellent polyurethane sole slurry catalyst. The polyurethane catalyst 1027 produced by our company has won unanimous praise and recognition in the market for its more suitable characteristics and more favorable price. Welcome to sample for free



**Features:**

1. Shorten demoulding time and increase production capacity.
2. Improve and optimize liquidity.
3. It is especially suitable for the catalyst of ethylene glycol system sole and self-skin microcellular foam system.

**Product Usage:**

1027 is a tertiary amine reaction delay catalyst, using ethylene glycol as a diluent;  
1027 prolongs the milking time, improves the fluidity, and at the same time guarantees the rapid demoulding;  
1027 is used as an efficient catalyst for carbamates in shoe sole applications.

**Storage and transportation:**

Should be sealed and stored in a dry, cool and ventilated warehouse

**package:**

200KG/drum Storage: It is recommended to store in a dry and cool area with proper ventilation. After the original packaging, please fasten the packaging cover as soon as possible to prevent the water and other substances from mixing into the product and affecting its performance. Do not breathe dust, avoid skin and mucous membrane contact. Smoking, eating and drinking are prohibited in the workplace. After work, shower and change clothes. Store contaminated clothing separately and wash it before reuse. Maintain good hygiene habits.

Company Name:	Newtop Chemical Materials (Shanghai) Co., Ltd.
Sales Manager:	Hunter
E-Mail:	<a href="mailto:Hunter@newtopchem.com">Hunter@newtopchem.com</a>
Tel:	+86 21-5161 9972
Mobile Phone:	+86-18301903153
Address:	Rm. 1104, No. 258, Songxing West Road, Baoshan District, Shanghai, China (Mainland)
Website:	<a href="http://www.newtopchem.com">www.newtopchem.com</a>

**FAQ**

Q1: May I get one sample before placing order?

Re: Yes, Sample are available. For normal products, samples are for free and you just need to bear the freight; For those high value products, you just need to freight and certain product cost. When we both cooperate for some times or when you are our VIP customer, free sample will be offered when you need.

Q2: Which payment is available for your company?

Re: T/T, L/C ,You can choose the one which is convenient for you.

Q3: How and when can I get my goods after payment?

Re: For small quantity products, they will be delivered to you by international courier(DHL, FedEx, TNT etc.)

or by air. Usually it will cost 3-5days that you can get the goods after delivery.For large quantity products, shipping by sea is worthwhile.It will cost days to weeks to come to your destination port, which depends on where the port is.

Q4: Is there any possible to use my appointed label or package?

Re: Yes. If needed, we'd like to use label or package according to your requirement.

Q5: How can you guarantee the goods you offer is qualified?

Re: We always believe honesty and responsibility are basis of one company, so whatever products we provide for you all are qualified.