

Methyl tin maleate powder C₆H₈O₄Sn Methyl tin maleate

Overview:

Product Name: Methyl tin maleate powder

Product designation: M-Maleate-P

Chinese name Methyl tin maleate

Foreign name Methyltin maleate

Appearance White powder

Tin content (%) 42.0±0.5

Item Index

Bulk density (g/cm) 1.0±0.1

Water content (%) ≤0.5

English name: Methyltin maleate

CAS number: -

Molecular formula: C₆H₈O₄Sn

项目	指标
锡含量 (%)	≥ 42
水含量 (%)	≤ 0.5

use:

White powder

Product properties: white amorphous powder. It is composed of maleic anhydride and methyl tin oxide. Slightly soluble in water. The product is applied to PVC heat stabilizer. It has excellent thermal stability and weather resistance, no sulfide pollution, no melting point when heated, and it will not reduce the softening point and impact force of hard products. The product lacks lubricity and has poor processing performance. Mainly used for PVC rigid products, ABS engineering plastics, condensation catalyst. The general dosage is: 0.5%-2%.



storage:

It should be kept dry during storage, and the temperature should be above 10 °C . The crystals are precipitated below 10°C, which will not affect the use effect after heating and melting.

transport:

Store in an airtight container in a cool, dry place. The storage place must be locked, and the key must be handed over to the technical experts and their assistants. The place of storage must be far away from oxidant and water source.

General-purpose plastic and plastic-sprayed iron drums or glass containers are packaged and transported in accordance with general chemical management regulations.

package:

Packing: It should be packed in glass containers, plastic containers, and metal containers resistant to chlorine corrosion, sealed and stored. Store in a cool, dry place, keep the container sealed and avoid contact with oxides. Do not breathe dust, avoid skin and mucous membrane contact. Smoking, eating and drinking are prohibited in the workplace. After work, shower and change clothes. Store contaminated clothing separately and wash it before reuse. Maintain good hygiene habits.

Company Name:	Newtop Chemical Materials (Shanghai) Co., Ltd.
Sales Manager:	Hunter
E_Mail:	Hunter@newtopchem.com
Tel:	+86 21-5161 9972
Mobile Phone:	+86-18301903153
Address:	Rm. 1104, No. 258, Songxing West Road, Baoshan District, Shanghai, China (Mainland)
Website:	www.newtopchem.com

FAQ

Q1: May I get one sample before placing order?

Re: Yes, Sample are available. For normal products, samples are for free and you just need to bear the freight; For those high value products, you just need to freight and certain product cost. When we both cooperate for some times or when you are our VIP customer, free sample will be offered when you need.

Q2: Which payment is available for your company?

Re: T/T, L/C ,You can choose the one which is convenient for you.

Q3: How and when can I get my goods after payment?

Re: For small quantity products, they will be delivered to you by international courier(DHL, FedEx, TNT etc.)

or by air. Usually it will cost 3-5days that you can get the goods after delivery. For large quantity products, shipping by sea is worthwhile. It will cost days to weeks to come to your destination port, which depends on

where the port is.

Q4: Is there any possible to use my appointed label or package?

Re: Yes. If needed, we'd like to use label or package according to your requirement.

Q5: How can you guarantee the goods you offer is qualified?

Re: We always believe honesty and responsibility are basis of one company, so whatever products we provide for you all are qualified.