

drier butyl tin oxide FASCAT 4101

Overview:

Chinese name: plasticizer, drier, butyl tin oxide, FASCAT 4101

Alias: FASCAT4101 catalyst, plasticizer drier, monobutyltin oxide, FASCAT 4101, CAS 13355-96-9, chloromonobutylstannic acid, chloride of monobutyltin oxide, chloromonobutylstannic acid

English name: FASCAT4101, Butyltin chloride, Butyltin chloride dihydroxide



Physical and chemical properties:

FASCAT[®]4101 is an amorphous, hydrolytically stable butyl tin chloride dihydroxide. It can be used for esterification, polycondensation and transesterification reactions. The catalyst is used to synthesize saturated polyester resin for powder coatings.

FASCAT[®] 4101 is used to produce unsaturated polyester resins for gel coating, sheet molding and casting molding applications. The temperature range of ester and antioxidant formation in the transesterification reaction is 140-180° C.

The production of PBT engineering resins for the automotive and construction markets requires the same temperature. It provides shorter esterification time, transesterification cycle time, lower reaction temperature and effective use of equipment.

CAS 13355-96-9

EC 236-406-1

Molecular formula C₄H₁₁ClO₂Sn

Specifications: different specifications, can be packaged according to customer needs

Product English name: Butylchlorodihydroxytin

CAS Number: 13355-96-9

EINECS Number: 13355-96-9

Alias: Chloride of monobutyl tin oxide

use:

Saturated polyester resin used in the synthesis of powder coatings.

Used in the production of unsaturated polyester resins for gel coating, sheet molding and casting molding applications.

Storage and transportation:

It should be sealed and stored in a dry, cool and ventilated warehouse.

package:

200KG/barrel Storage: It is recommended to store in a dry and cool area with proper ventilation. After the original packaging, please fasten the packaging cover as soon as possible to prevent the product performance from being mixed with other substances such as water resistance.

Store in a cool, dry place, keep the container tightly closed, and avoid contact with oxides. Do not inhale dust and avoid contact with skin and mucous membranes. Smoking, eating and drinking are prohibited in the workplace. After work, take a shower and change clothes. Store contaminated clothes separately and use them after washing. Maintain good hygiene habits.

Company Name:	Newtop Chemical Materials (Shanghai) Co., Ltd.
Sales Manager:	Hunter
E-Mail:	Hunter@newtopchem.com
Tel:	+86 21-5161 9972
Mobile Phone:	+86-18301903153
Address:	Rm. 1104, No. 258, Songxing West Road, Baoshan District, Shanghai, China (Mainland)
Website:	www.newtopchem.com

FAQ

Q1: May I get one sample before placing order?

Re: Yes, Sample are available. For normal products, samples are for free and you just need to bear the freight; For those high value products, you just need to freight and certain product cost. When we both cooperate for some times or when you are our VIP customer, free sample will be offered when you need.

Q2: Which payment is available for your company?

Re: T/T, L/C, You can choose the one which is convenient for you.

Q3: How and when can I get my goods after payment?

Re: For small quantity products, they will be delivered to you by international courier(DHL, FedEx, TNT etc.)

or by air. Usually it will cost 3-5days that you can get the goods after delivery.For large quantity products,

shipping by sea is worthwhile.It will cost days to weeks to come to your destination port, which depends on

where the port is.

Q4: Is there any possible to use my appointed label or package?

Re: Yes. If needed, we'd like to use label or package according to your requirement.

Q5: How can you guarantee the goods you offer is qualified?

Re: We always believe honesty and responsibility are basis of one company, so whatever products we provide for you all are qualified.